

Hotplates & Stirrers

Magnetic Stirrers (Scale & Digital & Multi-position Models)



MS-B / T with the included Plate Covers

► Features of MS-B, T, G Models

- Best-in-the-class with broad speed range and suitable for high-speed rotation experimental environment.
- Ergonomic designed, lightweight, easy to operate, and low profile.
- Wide top plate.
- Two non-slip silicon plate covers (white & black) provided for all MS-B, T, G Models.
- Non-slip strength rubber feet.
- Sparkless, silent and durable BLDC motor.
- Built-in thermal shutdown and current limit protection.



MS-G with the included Plate Covers

► Additional MS-G Features

- Bright and vivid VFD and responsive touch buttons.
- Gradual start-up to protect users against splashing of samples.
- M12 threaded hole to hold a support rod.

► Additional MS-M Features

- User-friendly operation and time setting modes allowing various ways of multi-position stirring to meet users' demands: single point, multiple point, whole row, whole column, etc.
- Easy-to-read VFD and intuitive control panel.
- Bright and vivid LED position indicating lamps.
- Non-slip see-through silicon plate mat. (optional)
- Chemical-resistant #304 grade stainless steel top-plate.
- Uncompromising safety devices.



MS-M with an optional Plate Mats

Included Accessories (without MS-M Models)

- Plate Covers (white & black)
- Magnetic Stirring Bars

Optional Accessories

- Silicone Plate Mats
- Plastic Retrievers

➡ see page 152-153

Hotplates & Stirrers

Magnetic Stirrers (Scale & Digital & Multi-position Models)

Specifications & Ordering Information



Model ¹⁾		MS-12B	MS-12T	MS-17B	MS-17T	MS-22B	
Technical Data	Speed Control	Electronic speed control					
	Stirring Capacity (Liter, H ₂ O)	2		4		5	
	Speed Range (RPM)	150 ~ 2,500					
	Speed Display	None					
	Motor Rating Input / Output (w)	2.9 / 1.6					
	Magnetic Bar (ØxL, mm / Inch), Max.	8×30 / 0.31×1.18	8×30 / 0.31×1.18	8×40 / 0.31×1.57	8×30 / 0.31×1.18	10×50 / 0.39×1.97	
Top Plate	Load, Max (kg / lbs)	15 / 33.07	10 / 22.05	20 / 44.09	20 / 44.09	25 / 55.12	
	Material	Polypropylene with non-slip silicon cover					
General Data	Dimension (mm / inch, Ø)	120 / 4.72	115 / 4.53	170 / 6.69	165 / 6.5	220 / 8.66	
	Body Material	Polypropylene					
	Dimension (mm / inch, WxDxH)	130×130×65 / 5.12×5.12×2.56	181×176×57 / 7.13×6.93×2.24	185×185×65 / 7.28×7.28×2.56	246×243×57 / 9.69×9.57×2.24	230×230×65 / 9.06×9.06×2.56	
	Weight (kg / lbs)	0.6 / 1.32		0.9 / 1.98		1.1 / 2.43	
	Electrical Requirements	AC 100 ~ 240V, 50 / 60Hz with power adapter					
	Power Consumption (w)	AC 100 ~ 240V, 50 / 60Hz					
Cat. No.	Protection Class (DIN EN 60529)	5		6			
	Persian Blue	KR plug	AAH330115BK	AAH333115BK	AAH330215BK	AAH333215BK	AAH330315BK
		US plug	AAH330115BU	AAH33316BU	AAH330215BU	AAH33326BU	AAH330315BU
	Yellow	KR plug	AAH330115YK	-	AAH330215YK	-	AAH330315YK
		US plug	AAH330115YU	-	AAH330215YU	-	AAH330315YU
	Orange	KR plug	-	AAH333115RK	-	AAH333215RK	-
US plug		-	AAH33316RU	-	AAH33326RU	-	

1) B-models: round type, T-models: triangle type.

Specifications & Ordering Information



	Model	MS-17G	MS-22G
Technical Data	Speed Control	Feedback control with PID	
	Stirring Capacity (Liter, H ₂ O)	4	5
	Speed Range (RPM)	30 to 2,000	
	Speed Display	VFD	
	Motor Rating Input / Output (W)	2.9 / 1.6	
	Magnetic Bar (ØxL, mm / Inch), Max.	8x40 / 0.31x1.57	10x50 / 0.39x1.97
Top Plate	Load, Max (kg / lbs)	20 / 44.09	25 / 55.12
	Material	Polypropylene with non-slip silicon cover	
General Data	Dimension (mm / inch, Ø)	170 / 6.69	220 / 8.66
	Body Material	Polypropylene	
	Dimension (mm / inch, WxDxH)	210x280x72 / 8.27x11.02x2.82	260x360x72 / 10.24x14.17x2.82
	Weight (kg / lbs)	1.35 / 2.98	1.75 / 3.86
	Electrical Requirements	AC 100 ~ 240V, 50 / 60Hz	
	Power Consumption (W)	6	
Cat. No.	Persian Blue	KR plug	AAH331215BK
		US plug	AAH331215BU
	Yellow	KR plug	AAH331215YK
		US plug	AAH331215YU
			AAH331315BK
			AAH331315BU

Specifications & Ordering Information



	Model	MS-23M	MS-32M	MS-33M	MS-51M	MS-52M	MS-53M
Technical Data	Speed Control	Feedback control with PID					
	Stirring Positions	6	6	9	5	10	15
	Speed Range (RPM)	30 to 2,000					
	Stirring Point Distance (mm / inch, WxD)	117x170 / 4.6x6.69	117x90 / 4.6x3.54	117x90 / 4.6x3.54	90 / 3.54	117x90 / 4.6x3.54	
	Timer	1 min. to 99 hours 59 min.					
	Speed Display	VFD					
	Motor Rating Input / Output (W)	2.9 / 1.6					
	Load, Max (kg / lbs)	30 / 66.14					
General Data	Dimension (mm / inch, WxDxH)	377x434x81 / 14.84x17.09x3.19	254x434x81 / 10x17.09x3.19	377x434x81 / 14.84x17.09x3.19	130x591x75 / 5.12x23.27x2.95	251x591x75 / 9.88x23.27x2.95	378x591x75 / 14.89x23.27x2.95
	Weight (kg / lbs)	6 / 13.23	5 / 11.02	7 / 15.43	4 / 8.82	8 / 17.64	11 / 24.25
	Electrical Requirements	AC 100 ~ 240V, 50 / 60Hz					
	Power Consumption (W)	45	45	54	45	85	135
Cat. No.	Protection Class (DIN EN 60529)	IP 21					
	KR plug	AAH332115K	AAH332215K	AAH332315K	AAH332415K	AAH332515K	AAH332615K
	US plug	AAH332115U	AAH332215U	AAH332315U	AAH332415U	AAH332515U	AAH332615U