

# D I G I T A L Alcohol Detector

# AlcoHAWK® PRO

**Quick Results**

**Easy  
To Use**

**FDA 510(k)  
Pre-Market Notification**

**Meets DOT/NHTSA  
Standards for Screeners**

**Portable**

**3 Digit  
LED Display**

**Displays Up To  
0.40% BAC**

**Multi-User  
Mouthpiece Design**



The AlcoHAWK® PRO takes the proven performance of the ABI sensor and platform and upgrades the air capture design to make it more fool proof and user friendly.



The AlcoHAWK® PRO includes *Sensor Recognition Technology™* to monitor certain types of abnormal sensor conditions.



The AlcoHAWK® PRO includes *FlowCheck Technology™* to ensure that subjects blow a large volume of air through the tester before displaying a test result.

**AlcoHAWK® PRO**

# Alcohol Detector *AlcoHAWK<sup>®</sup> PRO*

The AlcoHAWK<sup>®</sup> PRO is a breath alcohol screener that quickly screens for the presence of alcohol. The AlcoHAWK<sup>®</sup> PRO is lightweight and easy to use. Simply blow into the unit and within seconds the LED displays a digital readout. The AlcoHAWK<sup>®</sup> PRO includes *Sensor Recognition Technology<sup>™</sup>* to monitor certain types of abnormal sensor conditions. The AlcoHAWK<sup>®</sup> PRO also features new *FlowCheck Technology<sup>™</sup>* to monitor if a sufficient air volume is exhaled while testing.

## Features

- **Simple and easy to use**
- **Lightweight and compact**
- **Five replaceable mouthpieces (included)**
- **Elegant hard shell carrying case (included)**
- **Three-digit LED display**
- **Beeps when ready to use**
- **Beeps after breath sample obtained**
- **Accurate semi-conductor oxide sensor**
- **Advanced air pressure sensor**

## Specifications

|               |                                 |                  |                                     |
|---------------|---------------------------------|------------------|-------------------------------------|
| Dimensions    | 5 x 3.25 x 1 inches             | Digital Display  | 3 Digits (0.00% B.A.C.)             |
| Weight        | .5 lbs                          | Operating Temp   | 10 - 40° C (50-104° F)              |
| Housing       | Shock Resistant, Molded Plastic | Detection Range  | 0.00% - 0.40% B.A.C.                |
| Power         | 9 Volt Battery (included)       | Air Sample       | 5 Seconds                           |
| Battery Life  | 300 Tests <sup>1</sup>          | Calibration      | Required Periodically <sup>3</sup>  |
| Sensor        | Sensitive Semi-Conductor Sensor | Operation        | 1 Button                            |
| Blowing Time  | 5 Seconds                       | Limited Warranty | 1 Year                              |
| Response Time | 3 Seconds <sup>1</sup>          | Accuracy         | +/- 0.01 @ .02% B.A.C. <sup>2</sup> |

<sup>1</sup> Estimates, results may vary.

<sup>2</sup> Read owner's manual before use to understand proper use, accuracy, limitations, and calibration requirements.

<sup>3</sup> Visit [www.q3i.com](http://www.q3i.com) for calibration options.

<sup>4</sup> This device is not to be used to determine if the subject is legal or able to operate any equipment or vehicle.