

Stainless steel platform scale KERN SFB-H



Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]

Features

- 1 **Ideal for the robust industry**
- 2 Scale entirely out of stainless steel
- Load cell stainless steel**, silicone-coated.
Note: Silicone is not suitable for contact with aggressive substances such as acids etc. or for continuous use in wet areas.
- Stand** to elevate display device, standard, for models with weighing plate sizes
A height of stand approx. 200 mm
B height of stand approx. 400 mm
- Level indicator and foot screws** to level the balance precisely, fitted as standard, to give the most accurate weighing results

- Supports you in your HACCP-compliant quality system

Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of weighing plate (stainless steel) WxDxH A 300x240 mm B 400x300 mm, see larger picture
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 2 m
- Rechargeable battery pack internal, standard, operating time up to 80 h, charging time approx. 12 h

- Permissible ambient temperature 0 °C / 40 °C

Accessories

- Data interface RS-232**, interface cable included, approx. 1.5 m, must be ordered at purchase, KERN KFN-A01
- Suitable printers** see page 138

STANDARD

CAL EXT

GLP

PCS

TOL

IP 65

INOX

ACCU

230 V

DMS

1 DAY

3 YEARS WARRANTY

OPTION

DKD

+3 DAYS

FACTORY

RS 232

M

+3 DAYS

only SFB-HM

only with printer

Model	Weighing range [Max] kg	Readout [d] g	Verific. value [e] g	Minimum load [Min] g	Net weight approx. kg	Weighing plate		Options			
								Verification		DKD Calibr. Certificate	
								KERN		KERN	
SFB 10K1HIP	10	1	–	–	9	A		–		963-128	
SFB 20K2HIP	20	2	–	–	9	A		–		963-128	
SFB 50K5HIP	50	5	–	–	9	A		–		963-128	
SFB 50K5LHIP	50	5	–	–	14	B		–		963-128	
SFB 100K10HIP	100	10	–	–	13	B		–		963-129	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.											
SFB 15K5HIPM	15	5	5	100	9	A		965-228		963-128	
SFB 30K10HIPM	30	10	10	200	9	A		965-228		963-128	
SFB 60K20HIPM	60	20	20	400	9	A		965-229		963-129	
SFB 60K20LHIPM	60	20	20	400	14	B		965-229		963-129	
SFB 100K2HMM	150	50	50	1000	14	B		965-229		963-129	

New model

KERN Pictograms



Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).



Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.



Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.



Data interface RS-232: To connect the balance to a printer, PC or network.



RS 485 data interface: To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.



USB data interface: To connect the balance to a printer, PC or other peripheral devices.



Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripheral devices.



Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.



Interface for second balance: for direct connection of a second balance.



Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.



GLP/ISO record keeping: of weighing data with date, time and identification-no. Only with printers from KERN.



Piece counting: Reference quantities selectable. Display can be switched from piece to weight.



Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).



Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.



Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as bar-code and back calculation functions.



Percentage determination: Determining the deviation in % from the target value (100%).



Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.



Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.



Spray and dust protection IPxx: The type of protection is shown by the pictogram. For details see the glossary.



Stainless steel: the balance is protected against corrosion.



Suspended weighing: load support with hook on the underside of the balance.



Battery operation: Ready for battery operation. The battery type is specified for each device.



Rechargeable battery pack: rechargeable set.



Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.



Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.



Strain gauges: Electrical resistor on an elastic deforming body.



Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.



Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.



Single cell technology: Advanced version of the force compensation principle with the highest level of precision.



Verification possible: The time required for verification is specified in the pictogram.



DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.



Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.



Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.



Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high precision of your balance KERN offers you the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of its accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.

(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer: