

Ultrasonic thickness gauge SAUTER TU-US



Premium ultrasonic thickness gauge

Features

- **External sensor** for difficult-to-access measurements
- **Base plate for adjustment** included
- **1 Data interface RS-232**
- **2** Delivered in a hard carrying case
- **Scan mode** (10 measurements per sec.) or single point measuring mode possible
- **Internal memory** for up to 20 files (with up to 100 values per file)
- **Function to set limits:** Programmable high/low setpoints for go/no-go testing. Light and sound signal output
- Selectable measuring units: mm, inch

Technical data

- Precision: 0,5 % of [Max] ± 0,04 mm
- Dimensions LxWxH 132x76x32 mm
- Battery operation, batteries standard (2 x 1.5 V AA)
- Net weight approx. 345 g

Accessories

- **Software**, interface cable included, SAUTER ATU-04
- **External sensor**, 2,5 MHz, Ø 14 mm, for thick samples, in particular cast iron with rough upper surfaces: Measuring range 3 - 300 mm (steel), SAUTER ATU-US01
- **External sensor**, 7 MHz, Ø 6 mm, for thin test materials: Measuring range 0,75 - 80 mm (steel), SAUTER ATU-US02
- **External sensor**, 5 MHz, Ø 12 mm, for hot test materials: Measuring range (steel) 3 - 200 mm at temperatures of up to 300 °C, SAUTER ATB-US02
- **External sensor**, 5 MHz, Ø 10 mm, SAUTER ATU-US09
- **External sensor**, 5 MHz, Ø 10 mm, transducer at an angle of 90°, SAUTER ATU-US10
- **External sensor**, 6 MHz, Ø 6 mm, for thin test materials: Measuring range (steel) 1 - 50 mm, SAUTER ATB-US01
- **3 Thermal printer**, SAUTER ATU-05

STANDARD



OPTION



Model	Measuring range [Max] mm	Readout [d] mm	Sensor	Sound velocity m/sec	Option	
					ISO KERN	Calibr. Certificate
SAUTER TU 80-0.01US.	0,75 - 80	0,01	7 MHz Ø 6 mm	1000 - 9999	961-113	
TU 230-0.01US.	1,2 - 230	0,01	5 MHz Ø 10 mm	1000 - 9999	961-113	
TU 300-0.01US.	3 - 300	0,01	2,5 MHz Ø 14 mm	1000 - 9999	961-113	