

Mobile Leeb hardness tester SAUTER HMM



Advanced features for demanding applications

Features

- 1 Impact (rebound) sensor:** The bounce module is accelerated by a spring against the item being tested. Depending on how hard the object is, the kinetic energy of the module will be absorbed. The speed reduction will be measured and converted to Leeb hardness values.
- External impact sensor (Type D) included**
- Automatic recognition of the impact (rebound) sensor** connected to the HMM.
- Mobility:** The SAUTER HMM. provides a professional and resilient measurement solution wherever required, i.e. production, product control etc.
- All measurement directions possible (360°)** thanks to an automatic compensation function
- 2 Wireless IR printer** included for on-site printing of measurement protocols (battery operated)
- 3 Standard block included**

- 4 Delivered in a hard carrying case**
- Internal memory** for up to 9 data groups, with up to 9 values per group forming the average value of the group
- Mini statistics function:** Displays the measure value, the average value, the difference between the maximum and minimum values, date and time
- Measurement value display:** Rockwell (B & C), Vickers (HV), Brinell (HB), Shore (HSD), Leeb (HL), tensile strength (MPa)
- Automatic unit conversion:** The measuring result is automatically converted into all specified hardness units

- Minimum sample thickness: 8 mm
- Minimum sample radius (concave/convex): 50 mm (with support ring: 10 mm)
- Dimensions LxWxH 150x80x30 mm
- Mains adapter external standard
- Optional battery operation, batteries standard (3 x 1.5 V AAA), AUTO-OFF function to preserve the batteries, battery level indicator
- Net weight approx. 0,2 kg

06

Technical data

- Precision: 1 % at 800 HLD (± 6 HLD)
- Measuring range tensile strength: 375 - 2639 MPa (steel)
- Min. sample weight on a solid and stable support: 3 kg

Accessories

- 5 External impact sensor** Type DC. Short impact sensor for tests in holes or hollowed objects, SAUTER AHMO DC
- Attachment rings** for secure positioning, SAUTER AHMR 01
- Impact body**, SAUTER AHMO D01

STANDARD

OPTION

Model	Sensor	Readout	Option	
			ISO Calibr. Certificate	
SAUTER HMM.	Type D	[d] HL 1	ISO KERN 961-131	