

# Hanging scales KERN HCB · HCN



KERN HCB



KERN HCN

## The handy balance for higher loads - now up to 1 tonne!

### Features

- Ideal for rapid checking in goods receiving and shipping
- Also essential in the private sector for determining the weight of fish, game, fruits, bicycle parts, suitcases etc.
- **Data hold function:** For easy reading of the weight, the display can be „frozen“ in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key
- **Peak load display** (peak hold), measuring frequency 5 Hz


### Technical data

- LCD display, digit height 12 mm
- HCB:**
- **Ready for use:** Batteries included 3 x 1.5 V AA, operating time up to 300 h
  - **1 HCB** with [Max] ≥ 0,5 t: Reinforced version for heavy loads. Snap link and hook not included
- 2 HCN:**
- Housing stainless steel, IP65 protection
  - **Second display** on the rear of the balance
  - **Ready for use:** batteries 2 x 1.5 V AA standard, operating time up to 200 h

### Accessories for models with [Max] ≤ 200 kg

- **Hook (stainless steel)** standard, aperture approx. 25 mm, can be reordered, KERN HCB-A02
- **Snap link (stainless steel) with safety catch** standard, aperture approx. 15 mm, can be reordered, KERN HCB-A01

### STANDARD



### OPTION



| Model           | Weighing range [Max]<br>kg | Readout<br>[d]<br>g | Dimensions housing<br>WxDxH<br>mm | Height with snap link and hook<br>mm | Net weight approx.<br>kg |  | Option<br>DKD Calibr. Certificate |  |
|-----------------|----------------------------|---------------------|-----------------------------------|--------------------------------------|--------------------------|--|-----------------------------------|--|
|                 |                            |                     |                                   |                                      |                          |  | DKD<br>KERN                       |  |
| <b>KERN</b>     |                            |                     |                                   |                                      |                          |  |                                   |  |
| HCB 20K10       | 20                         | 10                  | 80x45x150                         | 290                                  | 0,4                      |  | 963-128                           |  |
| HCB 50K20       | 50                         | 20                  | 80x45x150                         | 290                                  | 0,4                      |  | 963-128                           |  |
| HCB 20K50 *     | 20                         | 50                  | 80x45x150                         | 290                                  | 0,4                      |  | 963-128                           |  |
| HCB 99K50       | 99                         | 50                  | 80x45x150                         | 290                                  | 0,4                      |  | 963-129                           |  |
| HCB 50K100      | 50                         | 100                 | 80x45x150                         | 290                                  | 0,4                      |  | 963-128                           |  |
| HCB 100K200     | 100                        | 200                 | 80x45x150                         | 290                                  | 0,4                      |  | 963-129                           |  |
| HCB 200K100     | 200                        | 100                 | 80x45x150                         | 290                                  | 0,4                      |  | 963-129                           |  |
| HCB 200K500     | 200                        | 500                 | 80x45x150                         | 290                                  | 0,4                      |  | 963-129                           |  |
| HCB 0.5T-3      | 500                        | 1000                | 82x42.5x152                       | -                                    | 0,35                     |  | 963-130                           |  |
| HCB 1T-3        | 1000                       | 2000                | 80x48x150                         | -                                    | 0,52                     |  | 963-130                           |  |
| stainless steel |                            |                     |                                   |                                      |                          |  |                                   |  |
| HCN 20K50IP     | 20                         | 50                  | 95x55x175                         | 315                                  | 0,8                      |  | 963-128                           |  |
| HCN 50K100IP    | 50                         | 100                 | 95x55x175                         | 315                                  | 0,8                      |  | 963-128                           |  |
| HCN 100K200IP   | 100                        | 200                 | 95x55x175                         | 315                                  | 0,8                      |  | 963-129                           |  |
| HCN 200K500IP   | 200                        | 500                 | 95x55x175                         | 315                                  | 0,8                      |  | 963-129                           |  |

! \* ONLY WHILE STOCKS LAST

■ New model

# KERN Pictograms



**Internal adjusting (CAL):** Quick setting of the balance's accuracy with internal adjusting weight (motordriven).



**Adjusting program (CAL):** For quick setting of the balance's accuracy. External adjusting weight required.



**Memory:** Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.



**Data interface RS-232:** To connect the balance to a printer, PC or network.



**RS 485 data interface:** To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.



**USB data interface:** To connect the balance to a printer, PC or other peripheral devices.



**Bluetooth data interface:** To transfer data from the balance to a printer, PC or other peripheral devices.



**Control outputs (optocoupler, digital I/O):** to connect relays, signal lamps, valves, etc.



**Interface for second balance:** for direct connection of a second balance.



**Network interface:** For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.



**GLP/ISO record keeping:** of weighing data with date, time and identification-no. Only with printers from KERN.



**Piece counting:** Reference quantities selectable. Display can be switched from piece to weight.



**Recipe level A:** Separate memory for the weight of the tare container and the recipe ingredients (net total).



**Recipe level B:** Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.



**Recipe level C:** Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as bar-code and back calculation functions.



**Percentage determination:** Determining the deviation in % from the target value (100%).



**Weighing units:** Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



**Weighing with tolerance range:** Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.



**Vibration-free weighing:** (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.



**Spray and dust protection IPxx:** The type of protection is shown by the pictogram. For details see the glossary.



**Stainless steel:** the balance is protected against corrosion.



**Suspended weighing:** load support with hook on the underside of the balance.



**Battery operation:** Ready for battery operation. The battery type is specified for each device.



**Rechargeable battery pack:** rechargeable set.



**Mains adapter:** 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.



**Power supply:** integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.



**Strain gauges:** Electrical resistor on an elastic deforming body.



**Tuning fork principle:** A resonating body is electromagnetically excited, causing it to oscillate.



**Electromagnetic force compensation:** Coil in a permanent magnet. For the most accurate weighings.



**Single cell technology:** Advanced version of the force compensation principle with the highest level of precision.



**Verification possible:** The time required for verification is specified in the pictogram.



**DKD calibration possible:** The time required for DKD calibration is shown in days in the pictogram.



**Package shipment:** The time required to manufacture the product internally is shown in days in the pictogram.



**Pallet shipment:** The time required to manufacture the product internally is shown in days in the pictogram.



**Warranty:** The warranty period is shown in the pictogram.

## Precision is our business

To ensure the high precision of your balance KERN offers you the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of its accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.

(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages  
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

## Your KERN specialist dealer: