



OZO 552



OZO 551



Trinocular tube

LAB LINE

The high-quality model for flexible and professional users

Features

- The KERN OZO-5 models are very robust and easy to use stereo microscopes with a zoom function operable from both sides for an above-average enlargement range.
- Their qualities, the flexible pillar stand and the optional integral, powerful and long-life LED incident and transmitted illumination make these models especially flexible.
- On all models it is possible to adjust the diopter on both tubes.
- A trinocular model version, allowing a camera to be fitted, is also available.
- These models are optimally suited to quality control, assembly and repair workstations in the electronics and semi-conductor industries as well as in biological laboratories and research establishments.
- These models are also ideal for use at workstations in rough working environments, such as training establishments, workshops and in production.
- The design of these special optical system allows a large depth of field, where only very little refocussing at the zoom enlargement is necessary.
- In addition, thanks to its precise resolution, it provides high-contrast images, an extra large field of view and is absolutely true-to-colour.
- These models offer the best possible ease of use thanks to their extra large working distance providing a large working surface.
- The multitude of auxiliary objectives, eyepieces, universal stands and additional accessory parts facilitates use in all common stereo microscopy applications.
- One of the central features of this variable and simultaneously robust series of microscopes is the stable and precisely adjustable mechanism. This is underlined by the functional and ergonomic design.

Technical data

- Optical system: Greenough
- Brightness adjustable
- Magnification ratio: 8,8:1
- Tube: 35° inclined
- Interpupillary distance: 52 – 76 mm
- Diopter adjustment (both-sided)
- Packing dimensions
WxDxH 370x330x385 mm

OZO 551 / OZM 553

- Net weight approx. 5,1 kg

OZM 552 / OZM 554

- Net weight approx. 6,1 kg

Please find detailed information in the following charts.

STANDARD



OPTION



Model KERN	Standard configuration						
	Tube	Eyepiece	Field of view mm	Objective Zoom	Stand	Illumination	
OZO 551	Binocular	HSWF 10x Ø 23 mm	Ø 28,75 – 3,3	0,8x – 7x	Pillar style	–	
OZO 552	Binocular	HSWF 10x Ø 23 mm	Ø 28,75 – 3,3	0,8x – 7x	Pillar style	3W LED (incident); 3W LED (transmitting)	
OZO 553	Trinocular	HSWF 10x Ø 23 mm	Ø 28,75 – 3,3	0,8x – 7x	Pillar style	–	
OZO 554	Trinocular	HSWF 10x Ø 23 mm	Ø 28,75 – 3,3	0,8x – 7x	Pillar style	3W LED (incident); 3W LED (transmitting)	

Eyepiece	Eigenschaften – Objektive						
	Magnification	Standard 1,0x	Auxiliary objectives				
			0,37x	0,5x	0,7x	1,5x	2x
HSWF 10x	Total magnification	8x – 70x	2,96x – 25,9x	4x – 35x	5,6x – 49x	12x – 105x	16x – 140x
	Field of view mm	Ø 28,75 – 3,3	Ø 74,3 – 8,5	Ø 57,5 – 6,6	Ø 41,1 – 4,7	Ø 19,2 – 2,2	Ø 14,4 – 1,6
SWF 15x	Total magnification	12x – 105x	4,44x – 38,9x	6x – 52,5x	8,4x – 73,5x	18x – 157,5x	24x – 210x
	Field of view mm	Ø 21,25 – 2,4	Ø 57,4 – 6,6	Ø 42,5 – 4,9	Ø 30,4 – 3,5	Ø 14,2 – 1,6	Ø 10,6 – 1,2
SWF 20x	Total magnification	16x – 140x	5,92x – 51,8x	8x – 70x	11,2x – 98x	24x – 210x	32x – 280x
	Field of view mm	Ø 17,5 – 2	Ø 47,3 – 5,4	Ø 35 – 4	Ø 25 – 2,9	Ø 11,7 – 1,3	Ø 8,75 – 1
SWF 30x	Total magnification	24x – 210x	8,88x – 77,7x	12x – 105x	16,8x – 147x	36x – 315x	48x – 420x
	Field of view mm	Ø 11,25 – 1,3	Ø 30,4 – 3,5	Ø 22,5 – 2,6	Ø 16,1 – 1,8	Ø 7,5 – 0,9	Ø 5,625 – 0,6
Working distance		108 mm	275 mm	195 mm	145 mm	50 mm	35 mm

Model outfit		Model KERN				Order number	
		OZO 551	OZO 552	OZO 553	OZO 554		
Eyepieces	HSWF 10x / Ø 23 mm	●●	●●	●●	●●	OZB-A5503	
	SWF 15x / Ø 17 mm	○○	○○	○○	○○	OZB-A5504	
	SWF 20x / Ø 14 mm	○○	○○	○○	○○	OZB-A5505	
	SWF 30x / Ø 9 mm	○○	○○	○○	○○	OZB-A5506	
	HSWF 10x / Ø 23 mm (reticule 0,1 mm)	○	○	○	○	OZB-A5512	
	SWF 15x / Ø 17 mm (reticule 0,05 mm)	○	○	○	○	OZB-A5513	
	SWF 20x / Ø 14 mm (reticule 0,05 mm)	○	○	○	○	OZB-A5514	
Achromatic auxiliary objectives	0,37x	○	○	○	○	OZB-A5611	
	0,5x	○	○	○	○	OZB-A5612	
	0,7x	○	○	○	○	OZB-A5613	
	1,5x	○	○	○	○	OZB-A5615	
	2,0x	○	○	○	○	OZB-A5616	
C-Mount	0,3x			○	○	OZB-A5701	
	0,5x			○	○	OZB-A5702	
	1,0x			○	○	OZB-A5703	
	1,0x (with micrometer)			○	○	OZB-A5704	
	for SLR cameras (Nikon)			○	○	OZB-A5706	
	for SLR cameras (Olympus)			○	○	OZB-A5707	
	for SLR cameras (Canon)			○	○	OZB-A5708	
Darkfield attachment	Darkfield attachment	○	○	○	○	OBB-A6201	
Object clamp	Object clamp	○	○	○	○	OBB-A6205	
Stands	Pillar style, without illumination	●		●			
	Pillar style, with 3W LED illumination (transmitting + incident)		●		●		
	Please find more stands in the catalogue on page 64 and on our website www.kern-sohn.com						
Stage plate	Frosted glass / Ø 94,5 mm		●		●	OZB-A5192	
	Black-white / Ø 94,5 mm	●	●	●	●	OZB-A5191	
	Glass / Ø 94,5 mm		○		○	OZB-A5190	
Mechanical stage	Stage size: WxD 188x160 mm, Travel: 76x65 mm, for transmitting and incident illumination	○	○	○	○	OZB-A5781	
	Stage size: WxD 180x175 mm, Travel: 100x86 mm, for incident illumination only	○	○	○	○	OZB-A5782	
External illumination	Please find the information about external illumination units in the catalogue from page 68 and on our website www.kern-sohn.com						

● = Standard configuration

○ = Option

 360°	360° rotatable microscope head	 FL-HBO	Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	 AUTO ATC	Automatic temperature compensation For measurements between 10 °C and 30 °C
 MONO	Monocular Microscope For the inspection with one eye	 FL-LED	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	 IP	Protection against dust and water splashes IPxx The type of protection is shown by the pictogram.
 BINO	Binocular Microscope For the inspection with both eyes	 PH	Phase contrast unit For a higher contrast	 BATT	Battery operation Ready for battery operation. The battery type is specified for each device.
 TRINO	Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	 POLAR	Polarising unit To polarise the light	 ACCU	Rechargeable battery pack Rechargeable set.
 ABBE	Abbe Condenser With high numerical aperture for the concentration and the focusing of light	 INFINITY	Infinity system Infinity corrected optical system	 230 V	Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
 HAL	Halogen illumination For pictures bright and rich in contrast	 ZOOM	Zoom magnification For stereomicroscopes	 230 V	Power supply Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
 LED	LED illumination Cold, energy saving and especially long-life illumination	 PARALLEL	Parallel optical system For stereomicroscopes, enables fatigue-proof working	 DAYS	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.
 IL	Incident illumination For non-transparent objects	 SCALE	Integrated scale In the eyepiece	 3 YEARS WARRANTY	Warranty The warranty period is shown in the pictogram.
 TL	Transmitting illumination For transparent objects	 USB 2.0	Integrated USB 2.0 digital camera For direct transmitting of the picture to a PC		
 FL	Fluorescence illumination For stereomicroscopes	 USB 3.0	Integrated USB 3.0 digital camera For direct transmitting of the picture to a PC		

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	N.A.	Numerical Aperture	W.D.	Working Distance
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR Kamera	Single-Lens Reflex camera	WF	Wide Field (Field number up to Ø 22 mm for 10x eyepiece)
LWD	Long Working Distance	SWF	Super Wide Field (Field number at least Ø 23 mm for 10x eyepiece)		

Your KERN specialist dealer: