

MAGNETIC STIRRERS



A new generation of stirrer for the most exacting work



Magnetic Stirrer “Agimin” without heating

MICROPROCESSOR CONTROLLED, ELECTRONIC CONTROL, PORTABLE.

FEATURES

Maximum stir volume 1 litre.
Speed controllable from 40 to 2000 r.p.m. with storage of the ultimate speed setting.
Double power source: 4 x 1.5V AA batteries or with a mains adapter.
Moulded ABS plastic case.
Excellent resistance to chemical agents.

CONTROL PANEL

Luminous On/Off push button.
Luminous r.p.m. push button.
Increase/ decrease speed push button.
Low battery indicator lamp.

MODEL

Part No.	Height cm	Ø cm	Depth cm	Power W	Weight Kg
7001731	5	10	15	0.9	0.35



Comes complete with support bar and clamp for 3 electrodes (1 x 13 mm Ø and 2 x 16 mm Ø), 4 batteries 1.5V AA, mains adapters and 2 PTFE coated stir bars.



Magnetic stirrer “Agimicro” without heating

FEATURES

Maximum stir volume: 2 Litres.
Adjustable stir speed from 40 to 1400 r.p.m.
Durable moulded ABS plastic body.
Excellent chemical resistance.

MODEL

Part No.	Height cm	Ø Plate cm	Power W	Weight Kg
7001638	5	12	2	0.5

Comes complete with a 8 Ø x 32 mm P.T.F.E. coated stir bar.

CONTROL PANEL

Mains switch with luminous “on” indicator.
Analogue control of speed in r.p.m.

ACCESSORIES

Support bar and electrode clamp (1 of 13 and 2 of 16 mm Ø). Used with pH and conductivity meters.
Part No. **7001639**



Powerful magnetic stirrer “Agimatic-H” without heating

FOR LOW VISCOSITY VOLUMES FROM 1 TO 60 LITRES.
USING REDUCED VOLUMES THE UNIT CAN STIR MEDIUM TO HIGH VISCOSITY LIQUIDS.

Maximum stirring power

FEATURES

Electronic speed control from 50 to 980 r.p.m., will maintain a constant stir speed irrespective of the liquid viscosity.
Digital speed display.
AISI 304 stainless steel top plate with an epoxy coated metal case.

MODEL

	Part No.	Speed control r.p.m.	Maximum stir volume in litres	Height/Width/Depth (exterior) cm	Power W	Weight Kg
AGIMATIC-HS	7001005	50 to 980	up to 25	12 28 34	35	8
AGIMATIC-HL	7001006	50 to 980	up to 60	14 44 38	40	12

Model HS comes complete with a 16 Ø x 127 mm stir bar and model HL with a 19 Ø x 150 mm stir bar.

CONTROL PANEL

Main switch with a luminous “on” indicator.
Electronic speed control.
Digital speed display in r.p.m.

