

Product Specifications

FlashCheck. Waterproof Lollipop Min/Max Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	1 second
Display Window Size	1.3 in W x 0.9 in H (32.9 mm W x 22.9 mm H)
Calibration	Auto calibration feature
Battery	Button Cell Alkaline
Body Casing	ABS plastic
Probe Length	4.13 in. (105 mm)
Probe Diameter	0.14 in. (3.56 mm), reduced tip 0.1 in (2.5mm)
Weight	1.3 oz (37.6g)
Waterproof Rating	IP65
Factory Calibration	NIST traceable calibration certified
Compliance Certificate	Manufacturers certificate of compliance available from DeltaTrak, NIST Traceable, NSF, CE



Model 11050

- NSF certified
- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B)).

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system



SS0008 15G1

